COMPUTER CONTROLLED INTERACTIVE TOUCH DISPLAY PAD WITH TRANSPARENT FULL CHARACTER KEYBOARD OVERLAYING DISPLAYED TEXT AND GRAPHICS

Technical Field

5   The present invention relates to user interactive computer supported display technology and particularly to such user interactive systems and methods related to touch screen technology.

Background of Related Art

10   In recent years, convergence of the data processing industry with the consumer electronics and communications industries has accelerated extensive consumer and business involvement in computer driven technologies. As a result of these changes, all aspects of work in

15   business and technology requires human/computer interfaces. There is a need to make computer directed activities accessible to a substantial portion of people who up to a few years ago, were computer illiterate, or at best, computer indifferent. In order for the

20   extensive computer supported market places to continue and be commercially productive, it will be necessary for a large segment of computer indifferent workers and consumers to be involved in computer interfaces. Thus, the challenge of technology is to create interfaces to

25   computers that are as close to the real world as possible.

In this connection, the mouse, which has been the primary input device to computers for a generation, is still considered to be a physically awkward input device.

30   Consequently, there has been considerable effort in the development of the touch screen or touch panel. It is

easy to use because it allows the user to point directly
to the display screen with his finger or a pen or stylus
to make selections that result in graphic or alphanumeric
changes on the display screen. The touch panel, in

5   various forms, has been in use for several years.
Several different technologies have been involved in
touch panels. Original touch panels used a series of
infrared LEDs and light sensors, such as photodiodes, to
provide low resolution panels of up to 50 resolvable

10   positions. The LEDs and sensors form a grid of invisible
light beams that the finger breaks to, thus, indicate its
position. The capacitively coupled touch panels were
able to develop a resolution of about 100 resolvable
positions. Higher resolution touch screens have been

15   developed using a variety of technologies from sound
waves reflected off fingers to conductive/resistive
layers separated by insulative material broken down by
touch.

Recent developments, which have dramatically

20   improved the clarity and resolution of liquid crystal
displays, as well as the improved resolution and
responsiveness in touch panels overlaid on such liquid
crystal displays, have renewed the hopes among students,
academics, researchers and literary developers for an

25   effective paperless notebook. Such a notebook should be
one which is light and portable; can store up to several
books, sequences of pages of which may be read via the
display screen; enables the entry of cursive drawings,
graphics and script, e.g. class or scientific notes and

30   annotations respective to the text and images; as well as
the entry of typed text.

The latter has presented a problem because for
greatest convenience it requires a full keyboard. This

has led to awkward notebook structures with a separate
swing-out touch keyboard not unlike laptop PCs. Also,
some touchpads have a separate keyboard apart from the
displayed text and graphics document for typed text

5   entries. Other simpler display notebooks have some
minimal pecking in of alphanumeric characters but not
from a full keyboard array.

Summary of the Present Invention
       The present invention provides a solution to the

10 above-mentioned shortcomings of touch screen display
notebooks by eliminating the hinged swing-out keyboard
while having a full keyboard available for the entry of
typed text, as well as a simultaneous display of the
text/graphics document being read or modified. To

15 achieve such results, the present invention provides a
portable computer controlled user interactive touch
responsive read/write display pad comprising the
combination of a display screen displaying text and
graphics, a transparent touch sensitive pad covering said

20 display screen, means responsive to cursive drawing or
characters touch input for displaying such drawing or
characters on said display screen, means for displaying a
full character keyboard on said display screen and means
responsive to touch inputs to characters on said keyboard

25 for displaying said touch keyboard inputs as text entries
within said displayed text and graphics.
       This full character keyboard is preferably
superimposed upon and transparent to said displayed text
and graphics in the displayed document. There is further

30 included means for selectively rendering either one of
said means responsive to cursive drawing or said means
responsive to inputs to touch keyboard non-interactive

while the other of said means remains interactive to thereby permit the unimpeded functioning of the means remaining interactive. In accordance with an aspect of the invention, there are means for varying the

5   transparentness of said superimposed keyboard whereby said keyboard is less transparent when said keyboard is interactive and more transparent when said keyboard is non-interactive.

There is also provided means responsive to an input

10   to a key in said keyboard for rendering interactive said means responsive to keyboard inputs and for rendering non-interactive said means responsive to cursive drawing.

Brief Description of the Drawings

The present invention will be better understood and

15   its numerous objects and advantages will become more apparent to those skilled in the art by reference to the following drawings, in conjunction with the accompanying specification, in which:

Fig. 1 is a block diagram of a data processing

20   system including a central processing unit, an LCD display and overlaid touch panel display that is capable of implementing the present invention;

Fig. 2 is a diagrammatic general three-dimensional view of the touch sensitive notebook of the present

25   invention;

Fig. 3 is a diagrammatic view of the notebook display screen of the present invention having a page of a book or document with text and graphics;

Fig. 4 is the diagrammatic view of the displayed

30   page of Fig. 3 during editing or cursive data entry via a stylus; in this mode the superimposed keyboard has a high transparentness;

Fig. 5 is the diagrammatic view of the displayed page of Fig. 3 during editing or text data entry via the keyboard; in this mode the superimposed keyboard has a relatively low transparentness;

5   Fig. 6 is a flowchart of the basic elements of the program in a computer controlled display system of this invention for coordinating the input to the touch display with the transparentness of the keyboard; and

Fig. 7 is a flowchart of the steps involved in an
10   illustrative run of data entry or document editing within the process set up in Fig. 6.

Detailed Description of the Preferred Embodiment

Referring to Fig. 1, a data processing system is shown which may function as the computer controlled
15   display terminal with the touch pad data entry display coupled to the primary display in accordance with the present invention. The computer controlled primary LCD display may be a LCD display personal computer unit made up of a central processing unit (CPU) 10, such as one of
20   the PC processors available from International Business Machines Corporation (IBM), Dell Corp. or Compaq Corp., which is provided and interconnected to various other components by system bus 12. An operating system 41 runs on CPU 10 and provides control and is used to coordinate
25   the functions of the various components of Fig. 1, including the touch screen 21 LCD display 23 pad which will hereinafter be described in greater detail. Operating system 41 may be one of the commercially available operating systems such as Microsoft Windows95™
30   or WindowsNT™, as well as UNIX or IBM's AIX operating systems. A program for simultaneously displaying the images of the primary display document or book on the

touch pad 21 display 23 and for applying the superimposed
transparent keyboard image to the LCD display,
application 40, to be subsequently described, runs in
conjunction with operating system 41 and provides output

5 calls to the operating system 41 which implement the
various functions to be performed by the application 40.
A read only memory (ROM) 16 is connected to CPU 10 via
bus 12 and includes the Basic Input/Output System (BIOS)
that controls the basic computer functions. Random

10 Access Memory (RAM) 14, I/O adapter 18 and communications
adapter 34 are also interconnected to system bus 12. It
should be noted that software components, including
operating system 41 and application 40, are loaded into
RAM 14, which is the computer system's main memory when

15 the system is in operation. Otherwise, when the system
is dormant, most of the software, including operating
system 40 and applications 41, are stored in disk storage
device 20. I/O adapter 18 may be a Small Computer System
Interface (SCSI) adapter that communicates with the disk

20 storage device 20, i.e. a hard drive. Communications
adapter 34 interconnects bus 12 with an outside network
enabling the data processing system to communicate with
other such systems over a Local Area Network (LAN) or
Wide Area Network (WAN), which includes, of course, the

25 Internet. Thus, the system of the present invention may
be used with screens and pages received over the
Internet. I/O devices, such as keyboard 24 and mouse 32,
are also connected to system bus 12 via user interface
adapter 22. It is through such input devices that the

30 user may make conventional data entries.

    With respect to the display pad input devices used
in the invention, any conventional touch screen display
may be used. Typically, in Fig. 1, there is an LCD

display having surface 23 upon which the visual output
from the computer is generated via pad display adapter
30. A touch sensitive display panel 21 is superimposed
upon display surface 23. This touch screen, which is
5   about 1/4" to 1/2" from surface 23, is responsive to a
touch stimulus, i.e. stylus 27, applied by the user to
make the graphic, cursive and other entries to be
subsequently described. The touch screen 21 resolution
is determined by digitizing circuitry (not shown) in a
10   touch screen adapter 25 to form a two-dimensional array
of discrete coordinate points. A touch stimulus applied
by stylus 27 or by the user's fingers in the superimposed
keyboard to any of the coordinate points is detected by a
sensor array (not shown) in the touch panel 21. The
15   sensor array generates an analog signal responsive to the
force imparted to the touch screen. The stimulus may
also be imparted proximate to the touch screen. The
signal is digitized by a sampling A to D convertor
circuit (not shown) in touch panel 21 to produce an input
20   data value. This data value, together with the
coordinates to which it relates, are transmitted from
touch panel 21 to touch pad display adapter 25. The
input data value corresponding to each set of coordinates
is conventionally refreshed by the A to D converter
25   circuit about 60 times a second. The touch pad adapter
25 connected to the bus architecture 12 passes each set
of coordinates to the bus architecture 12 to the CPU 10
and operating system 41 wherein this input is applied to
the LCD display 23 via LCD display adapter 30.
30   The touch panels or screens 21 may use any of the
standard technologies discussed above. In the present
embodiment, higher resolution panels using
resistive/conductive composites should provide best

results. Such structures use two slightly separated
layers of transparent material, one coated with a thin
layer of conductive material and the other with resistive
material. The pressure of the stylus forces the layers
5   to touch and the voltage drop across the resistive
substrate is measured and used to determine the
coordinates of the touched positions. There are many
such conductive/resistive touch screen displays on the
market that may be used in the implementation of the
10   present invention, such as the IBM 2489 Model 600 and PGI
Super Nightingale.

A three-dimensional view of the housing for the
notebook display of the present invention is shown in
Fig. 2. The notebook housing 45 includes touch sensitive
15   display screen 46 showing a page of a book or document
with printed text 47 and graphics 48. There is a
superimposed displayed keyboard 50 and some controls 51
for the notebook.

There will now be described a simple illustration of
20   the present invention with respect to the display screens
of Figs. 3 through 5. When the screen images are
described, it will be understood that these may be
rendered by storing image and text creation programs,
such as those in any conventional window operating system
25   in the RAM 14 of the system of Fig. 1. The operating
system is diagrammatically shown in Fig. 1 as operating
system 41. The display screens of Figs. 3 through 5 are
presented to the viewer on LCD display 23 of Fig. 1.

Fig. 3 shows an illustrative display screen during
30   a document or book reading session. The display may be
scrolled or paged conventionally. The screen 46 contains
text 47 and graphics 48. If the user decides to edit,
annotate or take class notes in his notebook, he may

switch into an edit mode as shown in Fig. 4 where he may
use pressure stylus 51 in the conventional manner to add
cursive notes 52 or cursive drawing or graphics 53.
During this edit session, a full keyboard 50 will appear.
5 The keyboard is transparent so that the user may still be
able to see the underlying text and graphics. Since the
editing in Fig. 4 is being done in the cursive mode, the
keyboard 50 has a high transparentness, i.e. it is a
"ghost" image to indicate its position and presence. The
10 operating system graphics may be set up so that the
keyboard entry edit mode for the entry of typed text is
switched to when the user hits any key in the keyboard.
Alternatively, one of the keys in the keyboard may be set
up to be the switch key. In the present example, "y" key
15 56 performs this role, i.e. the user must hit this key to
switch to the keyboard entry mode shown is Fig. 5. In
this keyboard entry mode, the keyboard 50 becomes less
transparent and more clearly defined for ease of use.
The keyboard is then used for entry of text 55 or for
20 keystroke editing 55. While stylus 51 does not function
during the keyboard entry mode of Fig. 5, it is included
in the figure just for illustrative comparison purposes.
In carrying out the functions of Figs. 4 and 5, the touch
responsive display pad may be set up to respond
25 conventionally to the stylus pressure. In the keyboard
mode of Fig. 5, pressure response programs may be set up
so that pressure applied at the positions of each of the
respective keys is translated to an image of the
character on the screen at the point of editing.
30   Now, with reference to Figs. 6 and 7, we will
describe a process implemented by the present invention
in conjunction with the flowcharts of these figures.
Fig. 6 is a flowchart showing the development of a

process according to the present invention for a touch
sensitive notebook with text entry via a superimposed
keyboard. A routine is set up for displaying documents
or books with graphics and text on a touch display, step

5   61. A routine is set up for entering cursive drawing and
script via a stylus into the displayed document, step 62.
A routine is provided for displaying a full character
keyboard on the touch display superimposed upon at least
a portion of the displayed text and graphics, step 63.

10 Means are provided for activating the transparent full
keyboard so that the touch sensitivity to the stylus is
rendered inactive when the keyboard is activated, step
64. A routine is provided for translating touches at the
key positions into corresponding text entered into the

15 displayed book or document, step 65. A routine is
provided for deactivating the keyboard and activating the
touch sensitivity to the stylus for cursive entries, step
66. A routine is also provided for increasing the
transparentness of the keyboard when the keyboard is

20 deactivated, step 67.

     The illustrative running of the process will now be
described with respect to Fig. 7. First, step 70, the
text/graphics document or book page is displayed. The
user selects the edit mode and the transparent keyboard

25 is displayed superimposed over the text/graphics, step
71. A determination is then made as to whether the user
has selected the keyboard text-entry mode of editing,
step 72. If Yes, the keyboard is made less transparent,
i.e. more clearly displayed, step 73, and desired text

30 entries are made in the document via the touch keyboard,
step 74. If the determination in step 72 is No, the
keyboard mode has not been selected, then step 45, the
keyboard is made more transparent, i.e. a "ghost"

outline, step 75, and stylus script and drawing entries
are made into the document, step 76. Upon the completion
of either a text, step 74, or a stylus entry, step 76,
function, a determination may conveniently be made as to

5   whether the session is at an end, step 77. If Yes, the
session is exited. If No, the session is returned to
step 72 where a further determination is made as to
whether the user has selected the keyboard text-entry
mode of editing and the process is repeated with respect

10 to the current or new page.

Although certain preferred embodiments have been
shown and described, it will be understood that many
changes and modifications may be made therein without
departing from the scope and intent of the appended

15 claims.